

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

THIS PAGE BLANK (uspto)




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G01N 35/10	A1	(11) International Publication Number: WO 98/21595 (43) International Publication Date: 22 May 1998 (22.05.98)
<p>(21) International Application Number: PCT/US97/20640</p> <p>(22) International Filing Date: 13 November 1997 (13.11.97)</p> <p>(30) Priority Data: 08/746,649 13 November 1996 (13.11.96) US</p> <p>(71) Applicant: BECKMAN INSTRUMENTS, INC. [US/US]; 2500 Harbor Boulevard, Fullerton, CA 92834-3100 (US).</p> <p>(72) Inventor: FARREN, Carl, A.; 5281 Hamer Lane, Placentia, CA 92870 (US).</p> <p>(74) Agents: MAY, William, H. et al.; Beckman Instruments, Inc., 2500 Harbor Boulevard, Fullerton, CA 92834-3100 (US).</p>	<p>(81) Designated States: AU, CA, CN, JP, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p>Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>	

(54) Title: **AUTOMATIC CHEMISTRY ANALYZER WITH SAMPLE CUP STOPPER PIERCING ASSEMBLY**

(57) Abstract

The invention provides an apparatus for piercing the cap of a container. The apparatus includes a blade support arm slidably attached to one or more vertical posts, a blade attached vertically below the blade support arm, and a cap retainer arm slidably attached to the vertical post such that the cap retainer arm is capable of travel along the posts between an upper position wherein the cap contacting surface is located above the elevation of the container cap and a lower position wherein the cap contacting surface is located at the elevation of the container cap. The cap retainer arm has an opening through which the blade can pass. A biasing member biases the cap retainer arm towards its lower position. The cap retainer arm is positioned below the blade but above the blade support arm contact surface. Thus, when the blade support arm slides upwardly, the blade support arm contacts the cap retainer arm and pushes the cap retainer arm upwardly from its lower position to its upper position.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

5

10

**AUTOMATIC CHEMISTRY ANALYZER WITH SAMPLE CUP
STOPPER PIERCING ASSEMBLY**

15

20

FIELD OF THE INVENTION

This invention generally relates to the field of automated clinical chemical analyzers, and specifically to high throughput automated chemical analyzers having automated sample container loading assemblies.

25

BACKGROUND OF THE INVENTION

30 A number of different automated clinical chemical analyzers are known in the art. Such analyzers range from simple, largely manually operated instruments to highly complex, nearly fully automated instruments. Each analyzer has its own particular performance characteristics related to the number ("menu") of different tests that the analyzer can perform and the number of samples that

35 can be processed in a given period of time ("throughput").

Large scale, highly complex analyzers useful in large hospitals and clinical laboratories have been developed which have both a large menu of tests which the instrument can perform and a high throughput. Such an analyzer is

5 described in U.S. Patent No. 4,965,049 issued to Lillig et al. which is incorporated herein by reference in its entirety.

Many such large scale, highly complex analyzers comprise an automated sample loading mechanism designed to mechanically transport sample
10 containers from a convenient loading location to a receiving site within the analyzer where liquid sample are extracted from the sample containers by suitable liquid extraction equipment. Such automated loading mechanisms minimize operator time required to operate such analyzers and therefore increase the operating efficiency of such analyzers.

15 A significant problem with automatic loading mechanisms of the prior art is that such automatic loading equipment are incapable of efficiently opening the sealed caps on the sample containers to allow the liquid extraction equipment to get at the sample within the container. Accordingly, the sealed
20 caps on the sample containers have to be opened manually. This requires an undue amount of operator time and markedly decreases the operating efficiency of the analyzer.

Accordingly, there is a need for a sample container cap piercing tool
25 which can be efficiently adapted into the automatic loading mechanism of a large scale, highly complex analyzer so that such automated loading mechanisms are fully automated.

SUMMARY OF THE INVENTION

30 The invention satisfies these needs. The invention is a combination for piercing a container cap disposed on the top of a container wherein the top of the container is disposed at a certain location L. The combination comprises:

- (a) a base;
- (b) a blade attached to a blade support arm, the blade support
35 arm being attached to the base such that the blade support arm is capable of movement between a first blade support arm position wherein the blade is

5 disposed spaced apart from the location L and a second blade support arm position wherein the blade is disposed immediately below location L;

(c) a cap retainer arm having a cap contacting surface capable of contacting and retaining the container cap, the cap retainer arm being attached to the base such that the cap retainer arm is capable of movement between a
10 first cap retainer arm position wherein the cap contacting surface is spaced apart from the location L and a second cap retainer arm position wherein the cap retaining surface is disposed substantially at the location L; and

(d) a motor for causing the serial movement of (i) the cap retainer arm from the first cap retainer arm position to the second cap retainer
15 arm position, (ii) the blade support arm from the first blade support arm position to the second blade support arm position, (iii) the blade support arm from the second blade support arm position to the first blade support arm position and (iv) the cap retainer arm from the second cap retainer arm position to the first cap retainer arm position;

20 so that, when a container cap is disposed at the cap retainer location L, the container cap can be serially (i) retained by the cap retainer arm, (ii) pierced by the blade, (iii) released from contact with the blade and (iv) released from contact with the cap retainer arm.

25 In a preferred embodiment, the combination comprises:

(a) a blade support arm slidably attached to a substantially vertical post such that the blade support arm is capable of travel along the vertical post between an upper blade support arm position, a middle blade support arm position and a lower blade support arm position, the blade support arm
30 having an upper contact surface and a lower contact surface;

(b) a blade attached to the blade support arm and disposed substantially vertically below the blade support arm, the blade being capable of piercing the container cap by downward movement of the blade;

(c) a cap retainer arm having a cap contacting surface capable
35 of contacting and retaining the container cap, the cap retainer arm being slidably attached to the vertical post such that the cap retainer arm is capable of travel

5 along the vertical post between the blade support arm upper contact surface and the blade support arm lower contact surface;

(d) a biasing member for biasing the cap retainer arm towards the blade support arm lower contact surface; and

(e) a motor for sliding the blade support arm up and down along
10 the vertical post between the upper blade support arm position, the middle blade support arm position and the lower blade support arm position;

wherein, (i) at the upper blade support arm position, the blade support arm lower contact surface retains the cap retainer arm so that the cap contacting surface is above location L, (ii) at the middle blade support arm
15 position, the cap contacting surface is allowed to contact a container cap disposed at location L but the blade is disposed higher than location L and (iii) at the lower blade support arm position, the cap contacting surface is allowed to contact a container cap disposed at location L and the blade is disposed immediately below location L.

20 In a typical embodiment, the blade support arm and the cap retainer arm are slidably attached to a pair of vertical posts which are fixed to the base and the biasing member comprises a pair of springs.

Preferably, the cap contacting surface of the cap retainer arm is
25 recessed to readily accept and retain the cap of the sample container.

The invention is advantageously encompassed into an automated diagnostic machine capable of determining at least one parameter of a liquid disposed within one or more capped sample containers disposed within a loading
30 area. Such a machine typically further comprises: (a) a body; (b) a sample station disposed within the body, the sample station being sized and dimensioned to retain a plurality of sample containers; (c) a reagent station disposed within the body, the reagent station being sized and dimensioned to retain a plurality of reagent containers; (d) an analyzing station disposed within the body, the
35 analyzing station comprising: (i) a reaction container and (ii) an analyzer for analyzing liquids disposed within the reaction container; (e) a sample transfer

5 apparatus for transferring liquid sample from the sample station and reagent from the reagent station to the reaction container; and (f) a sample container loading mechanism for transporting sample containers from a sample container loading area to the sample station.

10 In such a machine, it is preferable that suitable switching equipment is provided along the sample transfer apparatus so that the motor of the combination is operated automatically as sample containers are transferred into position within the combination.

15 The invention provides significant improvements over the prior art by providing an apparatus which allows operators of large scale, complex diagnostic analyzers to operate such analyzers in an almost fully automated mode without substantial operator time having to be expended in the preparation of containers containing samples for analysis.

20 DESCRIPTION OF THE DRAWINGS

These and other features, aspects and advantages of the present invention will become better understood with reference to the following description, appended claims and accompanying drawings where:

25 Figure 1 is a schematic plan view of an automated analyzing machine having features of the invention;

30 Figure 2 is a front view of an automated analyzing machine having features of the invention with its canopy closed;

Figure 3 is another front view of the automated analyzing machine of Figure 2 shown with its canopy open;

35 Figure 4A is a perspective of a sample container rack useful in the invention;

5

Figure 4B is a perspective view of a reaction cuvette useful in the invention;

10

Figure 4C is a cross-sectional side view of the reaction cuvette shown in Figure 4B;

Figure 5A is a perspective view of a sample probe arm assemble useful in the invention;

15

Figure 5B is a perspective view of a reagent probe arm assembly;

Figure 5C is a perspective view of a cup analyze probe arm assembly;

20

Figure 5D is a perspective view of a cuvette stirring rod assembly;

Figure 5E is a perspective view of a cuvette wash station;

25

Figure 6 is a flow diagram showing a reaction cup combination useful in the invention;

Figure 7 is a flow diagram showing an ion selective reaction cup assembly useful in the invention;

30

Figure 8 is an exploded perspective view of a sample cap piercing assembly having features of the invention;

Figure 9 is an end view of a blade useful in the sample cup piercing assembly shown in Figure 8;

35

Figure 10A is a cross-sectional side view of the sample cup piercing assembly shown in Figure 8, wherein the blade support arm is at the upper blade

5 support arm position;

Figure 10B is a cross-sectional side view of the sample cup piercing assembly shown in Figure 8, wherein the blade support arm is at the middle blade support arm position; and

10 Figure 10C is a cross-sectional side view of the sample cup piercing assembly shown in Figure 8, wherein the blade support arm is at the lower blade support arm position.

DETAILED DESCRIPTION

15 The following discussion describes in detail one embodiment of the invention and several variations of that embodiment. This discussion should not be construed, however, as limiting the invention to those particular embodiments. Practitioners skilled in the art will recognize numerous other embodiments as well. For a definition of the complete scope of the invention, the reader is directed to the appended claims.

20 Figures 1 - 3 show an automated analyzing machine 10 having features of the invention. The machine 10 comprises a body 12, a sample station 14, a reagent station 16, a random access analyzing station 18, a reaction cup analyzing station 20 and an ion selective electrode analyzing station 22.

25 The body 12 is typically a cabinet providing a housing for the various operative components. The body 12 is typically made from a lightweight metal such as a lightweight sheet steel. The embodiment shown in Figures 2 and 3 includes a hinged primary canopy 24. Figure 2 shows the analyzing machine 10 with the primary canopy 24 closed. Figure 2 shows the machine with the primary canopy 24 open.

35 Figures 2 and 3 also illustrate how a typical analyzing machine 10 of the invention can have an on-load tray cover 26, an off-load tray cover 28 and

5 one or more operator area covers **30** covering the sample station **14**, the reagent station **16**, the random access analyzing station **18**, the reaction cup analyzing station **20** and the ion selective electrode analyzing station **22**.

10 The sample station **14** is sized and dimensioned to retain a plurality of sample containers **32**. In the embodiment shown in Figures 1 - 3, the sample station **14** is a revolving circular carousel capable of retaining 40 sample containers **32** disposed in 10 sample container racks **34**. In a typical embodiment, each sample container **32** is a generally upright container having a container cap **36** of thin rubber or like material. A sample container rack **34**
15 containing four sample containers **32** useful in the invention is shown in Figure 4A. The sample station **14** is moveable by a rotating motor (not shown) such that each sample container **32** can be alternatively positioned under and moved away from at least one sample extraction site **38**.

20 The reagent station **16** is sized and dimensioned to retain a plurality of reagent containers **40**. Each reagent container **40** contains one or more compartments for retaining one or more different reagents useful in the analysis chemistry performed by the analyzing machine **10**. Also, it is preferable to predilute the reagent to minimize reagent usage and dilution step delays. A
25 preferred reagent container **40** design has three individual compartments and is described in detail in U.S. Patent Nos. 4,970,053 and 5,075,082, which are both incorporated herein by this reference in their entireties.

30 Preferably, the reagent station **16** is refrigerated, such as to a temperature of about 4°C, to preserve reagent life and minimize evaporation.

35 In the embodiment shown in Figures 1 - 3, the reagent station **16** is a revolving circular carousel. The reagent station **16** is movable by a rotating motor (not shown) such that each reagent container **40** can be alternatively positioned under and moved away from at least one reagent extraction site **42**.

5 Preferably, the reagent station **16** also includes a bar code reader (not shown) which reads bar-coded information printed on the reagent containers **40** and/or disposed on the reagent carousel. Such information can be transmitted to a computerized controller to assist in operation of the analyzing machine **10**.

10 The random access analyzing station **18** is sized and dimensioned to retain a plurality of reaction cuvettes **44** as illustrated in Figures 4B and 4C. In the embodiment shown in Figures 1 - 3, the random access analyzing station **18** is a revolving circular carousel capable of retaining in excess of 100 cuvettes **44**. Each cuvette **44** is a small open top reaction container having at least two
15 opposed transparent sides through which a beam of light can be directed.

 The random access analyzing station **18** further comprises random access analyzing station analyzer **46**, such as a nephelometer and/or photometer disposed proximate to a random access analyzing station analyzing site **48** for
20 determining at least one parameter of a sample disposed within the cuvettes **44**.

 The random access analyzing station **18** is movable by a rotating motor (not shown) such that each cuvette **44** can be alternatively positioned under and moved away from at least one cuvette sample deposit site **50**, at least
25 one cuvette reagent deposit site **52**, at least one cuvette mixing site **54**, at least one cuvette washing site **56** and the one random access analyzing station analyzing site **48**.

 The reaction cup analyzing station **20** comprises at least one
30 reaction cup module **58**. In the embodiment shown in Figure 1, the reaction cup analyzing station **20** comprises six reaction cup modules **58**. Each reaction cup module **58** can be used to measure high volume analyses such as analyses for sodium, potassium, glucose, creatinine and blood urea nitrogen.

35 Figure 6 illustrates a flow scheme for a typical reaction cup module. Reagent is provided to a reaction cup **332** via an inlet conduit **330** on one side of

5 the reaction cup module **58** (the right side on Figure 6). Reagent is pumped from a source of reagent **380** by the reagent pump **59** through remote controllable reagent valves **384** into the inlet conduit **330**. Within that portion of the inlet conduit **330** which is partially disposed within the reaction cup module **58**, reagent is heated by a heating element **326** before flowing into the reaction cup

10 **332**. Deionized rinse water is provided to the reaction cup **332** from a pressurized source of deionized water **348** through a remote controllable deionized water valve **386** and into the inlet conduit **330** on the side of the reaction cup module **58** opposite the inlet conduit **330** through which reagent flows into the reaction cup **332**. In that portion of the inlet conduit **330** which is

15 disposed within the reaction cup module **58**, deionized rinse water is heated by a second heating element **326** immediately prior to its flow into the reaction cup **332**.

The reaction cup **332** is drained via a drain line **388** through a

20 remote controllable master drain valve **390**. When the liquid to be drained is of a potentially hazardous sort, the liquid is drained to a suitable hazardous waste container **392** through a remote controllable hazardous waste container valve **394**. Where the liquid to be drained is of a non-hazardous sort, the liquid is drained to a suitable non-hazardous waste container **396** through a remote

25 controllable non-hazardous waste container valve **398**. Both the hazardous and non-hazardous waste containers **392** and **396** are typically maintained under vacuum to facilitate rapid and complete draining of liquid from the reaction cup **332**. Because a separate deionized rinse water source **348** is provided to the reaction cup **332**, such deionized rinse water is conveniently and inexpensively

30 used in the rinsing step. Moreover, because water is used in the rinse steps, much of the liquid drained from the reaction cup during the rinsing step can be disposed in a non-hazardous waste disposal area. Note further that because two separate heating elements **326** are used, time lags required for heating are much reduced. This is especially true in analysis operations requiring multiple rinse

35 cycles.

5 The use of the rinse water system also provides another substantial benefit over the prior art. The analyzing machine 10 using the cup analysis module 58 of the invention can be programmed to periodically and automatically recalibrate a nephelometer used as an analyzer 334, by briefly filling the reaction 332 cup with pure rinse water and calibrating the nephelometer to a
10 predetermined set point. This eliminates having to periodically shut down the machine 10 and manually calibrating each of the nephelometers used in the various reaction cup modules 58.

 A particularly useful reaction cup module 58 is disclosed in detail
15 U.S. Patent Application Serial No. _____, entitled _____, filed contemporaneously herewith, and which is incorporated herein by reference in its entirety.

 The ion selective electrode analyzing station 22 comprises a sample
20 injection cup 60 disposed in fluid tight communication with a flow cell analyzer 62 capable of measuring at least one electrolyte in a liquid sample. The ion selective electrode analyzing station 22 can be used to simultaneously analyze for sample electrolytes (and sample components which can be analyzed as electrolytes), such as sodium, potassium, calcium, chlorine and carbon dioxide.

25 Figure 7 illustrates a simplified flow scheme for a typical ion selective analyzing station 22. The sample injection cup 60 is disposed in fluid tight communication with an ion selective electrode analyzing station pump 64 capable of pumping at least one ion selective electrode analyzing reagent from a
30 source of such reagent (not shown) through the sample injection cup 60, through a valve V1, through the flow cell analyzer 62 and then to a suitable waste disposal site. Sample is pressured into the sample injection cup 60 via a cup analysis probe 138 (described below). In the sample injection cup, the sample is mixed with reagent as the reagent is pumped by pump 64 through the sample
35 injection cup 60 and is carried therewith through valve V1 and into the flow cell analyzer.

5
A CO₂ acid reagent pump **63** capable of pumping CO₂ acid reagent directly into the flow cell analyzer **62** is disposed in fluid tight communication with a source of CO₂ acid reagent (not shown). Also, an ion selective analyzing station reference solution pump **65** is disposed in fluid tight communication with a
10 source of reference solution (not shown). The ion selective electrode analyzing station reference solution pump **65** is capable of pumping reference solution through valve V2 directly into the flow cell analyzer **62**.

15 In a preferred embodiment, the ion selective electrode analyzing station pump **64**, the CO₂ acid reagent pump **63** and the ion selective electrode analyzing station reference solution pump **65** are driven by a single motor.

A particularly useful ion selective analyzing station **22** is disclosed in detail in U.S. Patent Application Serial No. _____, entitled
20 _____, filed contemporaneously herewith, and which is incorporated herein by reference in its entirety.

The analyzing machine **10** further comprises a motorized sample probe arm assembly **90** such as shown in Figure 5A. The sample probe arm
25 assembly **90** includes a sample probe arm **92** and a hollow sample probe **94**. The sample probe **94** has an internal chamber **96**, an open lower end **98** and an open upper end **100**. The sample probe **94** is disposed generally vertically in the sample probe arm **92** and is movable by a sample probe motor **102** between a lower sample probe position and an upper sample probe position.

30 The sample probe **94** can be equipped with a sample probe tip cleaning assembly **104** such as is described in U.S. Patent No. 5,408,891, the entirety of which is incorporated herein by this reference. Such cleaning assembly **104** includes a cleaning assembly chamber **106** connected in fluid tight
35 communication with a source of cleaning liquid **108** and a disposal site **110**.

5 The sample probe arm 92 is movable by a sample probe arm motor (not shown) between a first sample probe arm position wherein the sample probe is immediately above the sample extraction site 38 and a second sample probe arm position wherein the sample probe is immediately above the cuvette sample deposit site 50.

10 The sample probe 94 is connected to a sample probe pressure altering mechanism capable of alternatively applying a positive pressure and a negative pressure to the internal chamber 96 of the sample probe 94. Such pressure altering mechanism can be any of the various pressure altering mechanisms known in the art. Typically, such pressure altering mechanisms are provided by a syringe pump 112.

15 The sample probe arm assembly 90 is used to extract a predetermined quantity of sample from sample container 32 disposed within the sample station 14 at the sample extraction site 38 and transport that quantity of sample to a cuvette 44 disposed within the random access analyzing station 18 at the cuvette sample deposit site 50.

20 The analyzing machine 10 further comprises a motorized reagent probe arm assembly 114 such as shown in Figure 5B. The reagent probe arm assembly 114 includes a reagent probe arm 116 and a hollow reagent probe 118. The reagent probe 118 has an internal chamber 120, an open lower end 122 and an open upper end 124. The reagent probe 118 is disposed generally vertically in the reagent probe arm 116 and is movable by a reagent probe motor 126 between a lower reagent probe position and an upper reagent probe position.

25 The reagent probe arm 116 is movable by a reagent probe arm motor (not shown) between a first reagent probe arm position wherein the reagent probe 118 is immediately above the reagent extraction site 42 and a second reagent probe arm position wherein the reagent probe is immediately above the cuvette reagent deposit site 52.

5

10

The reagent probe **118** is connected to a reagent probe pressure altering mechanism capable of alternatively applying a positive pressure and a negative pressure to the internal chamber **120** of the reagent probe **118**. Such pressure altering mechanism can be any of the various pressure altering mechanisms known in the art. Typically, such pressure altering mechanisms are provided by a syringe pump **128**.

15

The reagent probe arm **116** is used to extract a predetermined quantity of reagent from a reagent container **40** disposed within the reagent station **16** at the reagent extraction site **42** and transport that quantity of reagent to a cuvette **44** disposed within the random access analyzing station **18** at the cuvette reagent deposit site **52**.

20

Both the sample probe arm **92** and the reagent probe arm **116** can include multiple independently movable probes. In the embodiment illustrated in the drawings, both the sample probe arm **92** and the reagent probe arm **116** comprise a pair of probes each independently movable about a primary axis of rotation **130**. Both probe arms are also rotatable as a whole about a secondary axis of rotation **132**.

25

30

The analyzing machine **10** further comprises a cup analysis probe arm assembly **134** such as shown in Figure 5C. The cup analysis probe arm assembly **134** includes a cup analysis probe arm **136** and a hollow cup analysis probe **138**. The cup analysis probe **138** has an internal chamber **140**, a lower end **142** and an open upper end **144**. The cup analysis probe **138** is disposed generally vertically in the cup analysis probe arm **136** and is movable by a cup analysis probe motor (not shown) between a lower cup analysis probe position and an upper analysis probe position.

35

The cup analysis probe **138** can be equipped with a cup analysis probe tip cleaning assembly **146** such as is known in the prior art. Such cleaning

5 assembly includes a cleaning assembly chamber **148** connected in fluid tight communication with a source of cleaning liquid **150** and a disposal site **152**.

The cup analysis probe arm **136** is movable by a cup analysis probe arm motor (not shown) between a first cup analysis probe arm position wherein the cup analysis probe is immediately above a sample container **32** in the sample station **14**, a second cup analysis probe arm position wherein the cup analysis probe **136** is immediately above one of the reaction cup modules **58** and a third cup analysis probe arm position wherein the cup analysis probe **136** is immediately above the sample injection cup **60**.

15 The cup analysis probe **136** is connected to a cup analysis probe pressure altering mechanism capable of alternatively applying a positive pressure and a negative pressure to the internal chamber **140** of the cup analysis probe **136**. Such pressure altering mechanism can be any of the various pressure
20 latering mechanisms known in the art. Typically, such pressure altering mechanisms are provided by a syringe pump **154**.

The cup analysis probe arm assembly **134** is used to extract a predetermined quantity of sample from a sample container **32** disposed within the sample station **14** and transport that quantity to each of the reaction cup modules **58** and to the sample injection cup **60**.

25 The analyzing machine **10** further comprises a cuvette stirring rod assembly **156** such as shown in Figure 5D. The cuvette stirring rod arm assembly **156** includes an elongate rotatable cuvette stirring rod **158** having a lower end **160** and an upper end **162**. The lower end **160** of the cuvette stirring rod includes a cuvette stirring rod paddle **164** attached thereto. The cuvette stirring rod is generally disposed vertically and is movable between a lower cuvette stirring rod position and an upper stirring rod position. The cuvette stirring rod arm assembly **156** is positionable above the cuvette mixing site **54**.
35 As illustrated by the embodiments shown in the drawings, the motorized cuvette

5 stirring rod assembly **156** can be an independent and separate assembly or it can be integrated with the sample probe arm **92** and/or the reagent probe arm **116**.

10 The analyzing machine **10** further comprises a cuvette wash station **166** as shown in Figure 5E. The cuvette wash station probe **168** is used to extract liquid reaction mixtures from the cuvettes **44**, dispose such mixtures to a suitable disposal site and then rinse and clean the cuvette **44** so that it can be used to analyze another quantity of sample.

15 The wash station **166** comprises one or more motorized cuvette wash station probes **168**. Each wash station probe **168** has an internal chamber **170**, an open lower end **172** and an open upper end **174**. The wash station probe **168** is disposed generally vertically above the cuvette washing site **56** in the random access analyzing station **18** and is movable by a wash station probe motor (not shown) between a lower wash station probe position and an upper wash station probe position.

20 In the embodiment shown in the drawings, the wash station probes **168** operated in pairs, one of each pair of wash station probes **168** being connected to a source of pressurized rinse solution and the other wash station probe **168** of each pair being connected to a disposal system adapted to vacuum out the contents of a cuvette and transfer such contents to a suitable disposal site.

25 Alternatively, each individual wash station probe **168** can be connected to a wash station probe pressure altering mechanism capable of alternatively applying a positive pressure and a negative pressure to the internal chamber **170** of the wash station probe **168**. The wash station probe pressure altering mechanism includes a mechanism for providing pressurized washing liquid from a source of washing liquid to the wash station probe **168** for washing a cuvette disposed at the cuvette washing site **56** and a mechanism for providing a negative pressure to the interior chamber **170** of the wash station probe **168** for

30

35

5 removing waste liquids from a cuvette disposed at the cuvette washing site **56** and for transferring such waste liquids to a disposal site. Such a mechanism for providing negative pressure to the interior chamber **170** typically comprises a source of vacuum.

10 Each of the pressure altering mechanism usable in the analyzing machine can further comprise an obstruction detector **176** comprising a pressure transducer operatively installed within the operative pressure transmitting conduits to alert the operator and/or shut down the machine should an obstructive pressure drop be detected within the pressure altering mechanism.

15 Such an obstruction detector **176** is described in detail in U.S. Patent Application Serial No. _____, entitled _____, filed _____, contemporaneously herewith, and which is incorporated herein in its entirety.

20 Typically, the automated analyzing machine **10** further comprises a controller **178** for controlling each of the various motors in a way which provides for the smooth, efficient and rapid operation of the machine **10**. The control is typically also used to retain and report analysis data. Preferably, the controller **178** comprises a digital computer which can be preprogrammed with a large

25 variety of operating instructions depending upon the samples being analyzed, the analyses to be run and the reagents at hand. Most preferably, the digital computer receives bar coded information regarding each of the samples to be analyzed, and the reagents in the reagent station **16** and uses that information to most efficiently conduct the analyses. Also, it is preferable that the controller

30 **178** keep track of the amounts of reagents used so as to alert the operator whenever reagent in any particular reagent container **40** begins to run low.

5

Also, it is preferable that the controller **178** include a "stat" mode, which gives the operator the ability to require the machine **10** to analyze particularly important samples in the reaction cup and ion selective electrode analyzing stations ahead of all other samples.

10

15

20

In the embodiment shown in the drawings, the analyzing machine **10** further comprises a sample container loading and preparation assembly **68**. The loading and preparation assembly **68** comprises a loading mechanism **70** for loading one or more sample containers from a loading area **72** to the sample station **14** along a loading mechanism path **74**. The loading mechanism **70** comprises an on-load tray **76** and an off-load tray **78**. In the embodiment shown in Figure 1, the on-load tray **76** and the off-load tray **78** are sized and dimensioned to retain a plurality of sample container racks **34**. The on-load tray **76** has a motorized loading arm **80** for pushing a plurality of sample container racks **34** towards the loading mechanism path **74**. The off-load tray **78** has a motorized unloading arm (not shown) for pushing the sample container racks **34** away from the loading mechanism path **74**.

25

30

The loading mechanism path **74** has a motorized loading path arm **82** which moves a single sample container rack **34** along the loading mechanism path **74** on to and off from the sample station **14**. A bar code reader **84** is typically disposed along the loading mechanism path **74**. The bar code reader **84** is capable of reading bar coded information disposed on each individual sample container **32** as the sample container **32** moves along the loading mechanism path **74**.

35

In the embodiment shown in Figure 1, the sample container loading and preparation assembly **68** further comprises a sample container cap piercing mechanism **86** capable of piercing the sample container caps **36** so as to leave the caps **36** open for access by the sample probe **94**. As illustrated in Figures 2 and 3, the sample container cap piercing mechanism **86** can be disposed under a

5 sample cap piercing mechanism cover 88.

Figures 8-10 illustrate a preferred embodiment of the sample container cap piercing mechanism 86 in detail. The sample cap piercing mechanism 86 comprises a base 400 having a fixed pair of vertical posts 402. Slidably attached to the two vertical posts 402 is a blade support arm 404. The blade support arm 404 has a lower blade support arm surface 406 and an upper blade support arm surface 408. Operatively disposed within the center of the blade support arm 404 is a drive element 410, such as a worm gear, for driving the blade support arm 404 up and down along the vertical posts 402.

15 Fixed within the blade support arm 404 is at least one blade 412. The blade 412 typically has a base 413 and a plurality of piercing sections 414. A preferred blade 412 has three or more piercing sections 414 disposed in vertical planes which intersect along a single axis 416, each such plane being spaced apart from adjoining planes by equal angles. Figure 10 illustrates a preferred blade 412 having four piercing sections 414 spaced apart from adjoining piercing sections 414 by 90°.

20 Preferably, each piercing sections 414 has the shape of a right triangle, wherein the point 418 is disposed further from the single axis 416 than any other portion of the piercing section 414.

Also slidably disposed along the vertical posts is a cap retainer arm 420. The cap retainer arm 420 has an upper cap retainer arm surface 422 and a lower retainer arm surface 424. The lower retainer arm surface 424 defines a cap retainer surface 426, which is preferably recessed to accept and retain the cap 36 on a sample container 32. The cap retainer arm 420 has openings 428 which are aligned with the blade 412 disposed within the blade support arm 404. Each opening 428 is large enough to allow the blade 412 to pass through the cap retainer arm 420.

5 As illustrated in Figures 10A, 10B and 10C, the blade support arm **404** is capable of traveling between an upper blade support position (illustrated in Figure 10A), a middle support arm position (illustrated in Figure 10B) and a lower blade support position (illustrated in Figure 10C), so as to pierce the cap **36** of a sample container **32** when the cap **36** is disposed at a location **L** which is at an elevation **E**.

10

 The blade support arm **404** has a lower contact surface **430** for contacting a lower portion of the cap retainer arm **420** and an upper contact surface **432** for contacting an upper portion of the cap retainer arm **420**. The cap retainer arm **420** is slidably attached to the vertical posts **402**, such that the cap retainer arm **420** is capable of traveling along the vertical posts **402** between the blade support arm upper contact surface **432** and the blade support arm lower contact surface **430**. At least one biasing member **434** is used to bias the cap retainer arm **420** towards the blade support arm lower contact surface **430**.

15

20

 A motor **436** is used to operate the drive element **410** to slide the blade support arm **404** up and down along the vertical posts **402** between the upper blade support arm position, the middle blade support arm position and the lower blade support arm position.

25

 As illustrated in Figure 10A, when the blade support arm **404** is in the upper blade support arm position, the blade support arm lower contact surface **430** engages the cap retainer arm **420** and retains the cap retainer arm **420** at an elevation spaced apart from the location **L** and above elevation **E**. Thus, when the blade support arm **404** is in the upper blade support arm position, sample containers **32** can be moved along the loading mechanism path **74** without being obstructed by the cap retainer arm **404**.

30

 As illustrated in Figure 10B, when the blade support arm **404** is lowered to the middle blade support arm position, the cap contacting surface **426** on the underside of the cap retainer arm **420** travels downwardly to the location

35

5 L. At this location, the cap contacting surface 426 is capable of contacting, engaging and retaining the cap 36 on the top of a sample container 32 disposed along the loading mechanism path 74. Because of the downward pressure provided by the biasing member 434, the cap retainer arm 420 firmly retains the sample container 32 in place during the remainder of the cycle wherein the
10 sample container cap 36 is pierced by the blade 412. Preferably, the cap contacting surface 426 is recessed to facilitate the engaging and retaining of the sample container cap 36.

At the moment when the cap contacting surface 426 contacts the
15 sample container cap 36, when the blade support arm is at the middle blade support arm 404 position, the blade 412 is disposed apart from the location L, above elevation E, and, therefore, does not (yet) penetrate the sample container cap 36. However, as the blade support arm 404 continues downwardly from the middle blade support arm position to the lower blade support arm position, the
20 blade 412 travels through the opening 428 in the cap retainer arm 420 to an elevation below E immediately below the location L, thereby piercing the sample container cap 36 with the piercing sections 44 of the blade 412.

Typically, the downward travel of the blade support arm 404 is
25 terminated when the blade support arm upper contact surface 432 contacts the cap retainer arm 420.

After the sample container cap 36 has been pierced, the motor 436 causes the blade support arm 404 to slide upwardly along the posts 402 to the
30 upper blade support arm position. This action causes the lower contact surface 430 of the blade support arm 404 to push the cap retainer arm 420 upwardly against the biasing pressure of the biasing member 434 to an elevation above elevation E. The sample container 32 -- now having a pierced sample container cap 36 -- is thereby freed up so that it can be further moved along the loading
35 mechanism path 74 to the sample station 14.

5 In operation, the operator of the automated analyzing machine of the invention 10 places samples to be analyzed in individual sample containers 32 and places each sample container 32 in one or more sample container racks 34. The sample container racks 34 are placed in the on-load tray 76.

10 The motorized loading arm 80 pushes sample container racks 34 in the on-load tray 76 towards the loading mechanism path 74. As each sample container rack 34 enters the loading mechanism path 74, the motorized loading path arm 82 pushes the sample container rack 34 along the loading mechanism path 74 towards the sample station 14.

15 As the sample containers 32 pass by the bar code reader 84, bar-coded information appended to each sample container 32 is read by the bar code reader 84 and is transmitted to the controller 178. Such bar code coded information typically includes the identity of the sample and the analyses which are to be run using individual portions of the sample.

20 As the sample container rack 34 is pushed further along the loading mechanism path 74, it passes under the cap piercing mechanism 86 to the location L. The cap piercing mechanism 86 thereat pierces the caps 36 on each of the sample containers 32.

25 The sample container rack 34 then is pushed further along the leading mechanism path 74 to the sample station 14 wherein a clamping mechanism within the sample station 14 holds the sample container rack 34 firmly upright.

30 The sample station 14 is rotated under the control of the controller 178. When an individual sample container 32 is placed at a sample extraction site 38, a small quantity of the sample is extracted from the sample container 32 by the sample probe 94. This is accomplished by positioning the sample probe 94 above the sample extraction site 38, lowering the sample probe 94 to the

5 lower sample probe position wherein the open-ended lower end **98** of the sample probe **94** is placed below the surface of the sample within the sample container **32**. A small quantity of the sample is then extracted into the sample probe internal chamber **96** by drawing a vacuum on the sample probe internal chamber **96** using the sample probe pressure altering mechanism. The sample probe **94** is
10 then raised to the upper sample probe position and the sample probe arm **92** moves the sample probe **94** to a position where it is directly above the cuvette sample deposit site **50**.

At the cuvette sample deposit site **50**, the sample probe **94** is again
15 lowered to the lower sample probe position and the quantity of sample within the sample probe **94** is deposited into a cuvette **44** positioned at the cuvette sample deposit site **50**. This is done by creating a slight elevated pressure within the sample probe internal chamber **96** using the sample probe pressure altering mechanism. The lower end of the sample probe **94** is then retracted into the
20 sample probe tip cleaning assembly **104** where it is rinsed using cleaning liquid from the source of cleaning liquid **108**. After cleaning, the cleaning liquid is flushed to a suitable disposal site **110**. The sample probe **94** is then ready to extract another quantity of sample from another sample container **32**.

25 Contemporaneously with the above-described action of the sample probe **94**, the reagent probe **118** is used in similar fashion to extract a quantity of an appropriate pre-mixed reagent from the reagent station **16** and depositing that quantity of reagent into the cuvette **44**. Usually the reagent is added to the cuvette immediately prior to the deposit of the sample within the cuvette **44**.

30 After sample and reagent are both added to the cuvette **44**, the cuvette **44** is rotated to the cuvette mixing site **54**. At the cuvette mixing site **54**, the cuvette stirring rod **158** is lowered to the lower cuvette stirring rod position and the stirring rod paddle **164** is rotated so as to agitate and thoroughly
35 mix the sample and reagent within the cuvette **44**.

5 In typical random access analyzing operations wherein analyses are carried out at an elevated temperature, the mixture of sample and reagent within the cuvette 44 is then allowed to stand within the random access analyzing station 18 while the mixture is brought up to temperature, such as by blowing heated air through the random access analyzing station 18. When the mixture
10 within the cuvette 44 has reached proper temperature, the contents of the cuvette 44 are analyzed using the random access analyzing station analyzer 46. In a preferred operation, the cuvette 44 is placed at the random access analyzing station analyzing site 46 a plurality of times and is thereby analyzed a plurality of times so that the reportable results are derived from an average of the plurality of
15 analyses. The reportable results are thereby extremely reliable.

 After analyses are completed regarding the mixture within the cuvette 44, the cuvette 44 is moved to the cuvette washing site 56 at the cuvette wash station 166. At the cuvette wash station 166, a wash station
20 probe 168 is moved from its upper probe position to the lower probe position and the reaction mixture is extracted using the wash station pressure altering mechanism. Depending upon the kind of mixture which had been analyzed within the cuvette 44, the cuvette 44 is then rinsed once or several times using
25 pressurized washing liquid. After the rinse liquid is removed from the cuvette 44 and sent to suitable disposal, the cuvette 44 is ready to accept another sample for analysis.

 Contemporaneously with the operation of the random access analyzing station 18, high volume analyses are performed in the reaction cup
30 analyzing station 20 and in the ion selective electrode analyzing station 22. First, a predetermined quantity of an appropriate reagent is pumped into each reaction cup 332 and into the injection sample cup 60 using the reagent pump 59. The magnetic stirrer is engaged. Then, the cup analysis probe arm assembly 134
35 positions the cup analysis probe 136 above a sample container 32 within the sample station 14, the cup analysis probe 136 is lowered to the lower probe position and a relatively large quantity of sample is extracted into the internal

5 chamber 140 within the cup analysis probe 138 using the cup analysis probe pressure altering mechanism. The cup analysis probe 138 is then raised to the upper probe position and the cup analysis probe arm 136 moves the cup analysis probe 138 to a position directly above one of the reaction cup modules 58. The cup analysis probe 138 is lowered to the lower cup position and a portion of the
10 sample within the cup analysis probe 138 is deposited within the reaction cup 332. The cup analysis probe 138 is then again raised to the upper probe position and the cup analysis probe arm 136 moves the cup analysis probe 138 to immediately above each of the other reaction cup modules 58 and deposits a portion of the sample within each such reaction cups 332.

15 When all of the reaction cups 332 are filled, the cup analysis probe arm 136 moves the cup analysis probe 138 to directly above the sample injection cup 60. The cup analysis probe 138 is again lowered to the lower probe position and the remainder of the sample is deposited within the injection sample cup 60.

20 After the mixture of reagent and sample is thoroughly mixed by the magnetic stirrer, the mixture is analyzed using the reaction cup analyzing station analyzer 334 in each cup module, and the results of the analyses are reported to the controller 178. The reaction cups 332 are then rinsed and ready for another
25 sample.

30 Contemporaneously, in the ion specific electrode analysis station, the quantity of sample within the injection sample cup 60 is thoroughly flow mixed with the reagent. After the sample and reagent are properly mixed, the mixture is passed through the flow cell 62 where individual electrodes within the flow cell 62 each perform a single analysis on the mixture. The results of the analysis are reported to the controller 178. The mixture is then drained to a suitable disposal site 66 and the system is rinsed in preparation for the analysis of another sample.

5

10

After the sample within each of the sample containers 32 in a sample container rack 34 are analyzed, the sample container rack 34 is removed from the sample station 14 using the motorized loading path arm 82. The sample container rack 34 is retracted along the loading mechanism path 74 to the off-load tray 78. Once in the off-load tray 78, the motorized unloading arm pushes the sample container rack 34 towards the end of the off-load tray 78 where it is removed by the operator.

15

The invention provides significant improvements over the prior art by reducing throughput times, maintenance costs and operating expense, while increasing accuracy and reliability.

20

Although the present invention has been described in considerable detail with reference to certain preferred versions thereof, other versions are possible. Therefore, the spirit and scope of the appended claims should not be limited to the description of the preferred versions contained herein.

5 **What is Claimed is:**

1. A combination for piercing a container cap disposed on the top of a container at a location L, the combination comprising:

(a) a base;

10 (b) a blade attached to a blade support arm, the blade support arm being attached to the base such that the blade support arm is capable of movement between a first blade support arm position wherein the blade is disposed spaced apart from the location L and a second blade support arm position wherein the blade is disposed immediately below location L;

15 (c) a cap retainer arm having a cap contacting surface capable of contacting and retaining the container cap, the cap retainer arm being attached to the base such that the cap retainer arm is capable of movement between a first cap retainer arm position wherein the cap contacting surface is spaced apart from the location L and a second cap retainer arm position wherein the cap retaining surface is disposed substantially at the location L; and

20 (d) a motor for causing the serial movement of (i) the cap retainer arm from the first cap retainer arm position to the second cap retainer arm position, (ii) the blade support arm from the first blade support arm position to the second blade support arm position, (iii) the blade support arm from the
25 second blade support arm position to the first blade support arm position and (iv) the cap retainer arm from the second cap retainer arm position to the first cap retainer arm position;

so that, when a container cap is disposed at the cap retainer location L, the container cap can be serially (i) retained by the cap retainer arm,
30 (ii) pierced by the blade, (iii) released from contact with the blade and (iv) released from contact with the cap retainer arm.

2. A combination for piercing a container cap disposed on the top of a container at an elevation E, the combination comprising:

35 (a) a blade support arm slidably attached to a substantially vertical post such that the blade support arm is capable of travel along the

5 vertical post between an upper blade support arm position; a middle blade support arm position and a lower blade support arm position, the blade support arm having an upper contact surface and a lower contact surface;

(b) a blade attached to the blade support arm and disposed substantially vertically below the blade support arm, the blade being capable of
10 piercing the container cap by downward movement of the blade;

(c) a cap retainer arm having a cap contacting surface capable of contacting and retaining the container cap, the cap retainer arm being slidably attached to the vertical post such that the cap retainer arm is capable of travel along the vertical post between the blade support arm upper contact surface and
15 the blade support arm lower contact surface;

(d) a biasing member for biasing the cap retainer arm towards the blade support arm lower contact surface; and

(e) a motor for sliding the blade support arm up and down along the vertical post between the upper blade support arm position, the middle blade support arm position and the lower blade support arm position;
20

wherein, (i) at the upper blade support arm position, the blade support arm lower contact surface retains the cap retainer arm so that the cap contacting surface is higher than E, (ii) at the middle blade support arm position, the cap contacting surface is allowed to contact a container cap disposed at E
25 but the blade is disposed higher than E and (iii) at the lower blade support arm position, the cap contacting surface is allowed to contact a container cap disposed at E and the blade is disposed below E.

3. The combination of claim 2 wherein the blade support arm and the
30 cap retainer arm are slidably attached to a pair of substantially vertical posts disposed in parallel.

4. The combination of claim 2 wherein the biasing member comprises at least one spring.

5. The combination of claim 2 wherein the cap contacting surface of
35

5 the cap retainer arm is recessed.

6. The combination of claim 2 wherein the blade comprises three or more piercing sections, each piercing section being disposed in a vertical plane and all of the vertical planes being disposed so that they intersect along a single vertical axis with each plane being spaced apart from adjoining planes by equal
10 angles.

7. The combination of claim 6 wherein each piercing section comprises a point which has the shape of a right triangle and wherein the point of each piercing section is disposed further from the single vertical axis than any
15 other portion of the piercing section.

8. The combination of claim 6 wherein the blade comprises four piercing sections, each spaced apart from adjoining piercing sections by about 90
20 degrees.

9. A device for determining at least one parameter of a the liquid in one or more a capped sample containers disposed in a loading area, the device comprising:

25 (a) a body;

(b) a sample station disposed within the body, the sample station being sized and dimensioned to retain a plurality of sample containers;

(c) a reagent station disposed within the body, the reagent station being sized and dimensioned to retain a plurality of reagent containers;

30 (d) an analyzing station disposed within the body, the analyzing station comprising: (1) a reaction container and (2) an analyzer for analyzing liquids disposed within the reaction container;

(e) a sample transfer mechanism for transferring liquid sample from the sample station and reagent from the reagent station to the reaction
35 container; and

(f) a sample container loading and preparation assembly

5 comprising (1) a loading mechanism for moving one or more vertically disposed capped sample containers from the loading area to the sample station along a loading mechanism path, wherein the location of the caps of the sample containers is at L, and (2) a combination for piercing the cap of the sample containers disposed along the loading mechanism path, such combination
10 comprising:

(i) a base;

a blade attached to a blade support arm, the blade support arm being attached to the base such that the blade support arm is capable of movement between a first blade support arm position wherein the blade is disposed spaced apart from the location L and a second blade support arm position wherein the blade is disposed immediately below location L;

(ii) a cap retainer arm having a cap contacting

surface capable of contacting and retaining the container cap, the cap retainer arm being attached to the base such that the cap retainer arm is capable of movement between a first cap retainer arm position wherein the cap contacting surface is spaced apart from the location L and a second cap retainer arm position wherein the cap retaining surface is disposed substantially at the location L;
25 and

(iii) a motor for causing the serial movement of (I)

the cap retainer arm from the first cap retainer arm position to the second cap retainer arm position, (II) the blade support arm from the first blade support arm position to the second blade support arm position, (III) the blade support arm from the second blade support arm position to the first blade support arm position and (IV) the cap retainer arm from the second cap retainer arm position to the first cap retainer arm position;

35 so that, when a container cap is disposed at the cap retainer location L, the container cap can be serially (1) retained by the cap retainer arm, (2) pierced by the blade, (3) released from contact with the blade and (4) released

5 from contact with the cap retainer arm.

10 10. The combination of claim 9 wherein the blade support arm and the cap retainer arm are slidably attached to a pair of substantially vertical posts disposed in parallel.

15 11. The combination of claim 9 wherein the blade comprises three or more piercing sections, each piercing section being disposed in a vertical plane and all of the vertical planes being disposed so that they intersect along a single vertical axis with each plane being spaced apart from adjoining planes by equal angles.

20 12. The combination of claim 9 wherein each piercing section comprises a point which has the shape of a right triangle and wherein the point of each piercing section is disposed further from the single vertical axis than any other portion of the piercing section.

25 13. A device for determining at least one parameter of a the liquid in one or more capped sample containers disposed in a loading area, the device comprising:

- 30 (a) a body;
- (b) a motorized sample station disposed within the body, the sample station being sized and dimensioned to retain a plurality of sample containers and having a sample extraction site, the sample station being movable within the body such that, when the sample station retains a plurality of sample containers, individual sample containers can alternatively be moved to and away from the sample extraction site;
- 35 (c) a motorized reagent station disposed within the body, the reagent station being sized and dimensioned to retain a plurality of reagent containers and having a reagent extraction site, the reagent station being movable within the body such that, when the reagent station retains a plurality of reagent containers, individual reagent containers can alternatively be moved to and away

5 from the reagent extraction site;

(d) a motorized random access analyzing station disposed within the body, the random access analyzing station being sized and dimensioned to retain a plurality of cuvettes and having a cuvette sample deposit site, a cuvette reagent deposit site, a cuvette mixing site, a cuvette washing site, a random access analyzing station analyzing site and an analyzer disposed proximate to the random access analyzing station analyzing site for determining at least one parameter of a sample disposed within the cuvettes; the random access analyzing station being movable within the body such that, when the random access analyzing station retains a plurality of cuvettes, individual cuvettes can alternatively be moved to and away from (1) the cuvette mixing site, (2) the cuvette washing site and (3) the random access analyzing station analyzing site;

(e) a reaction cup analyzing station disposed within the body, the reaction cup analyzing station comprising: (1) a reaction cup, (2) an analyzer for analyzing liquids disposed within the reaction cup and (3) a reaction cup analyzing station pump mechanism for pumping reaction cup analyzing station reagent from a source of reaction cup analyzing station reagent to the reaction cup and for pumping the contents of the reaction cup to a suitable disposal site;

(f) an ion selective electrode analyzing station disposed within the body, the ion selective analyzing station comprising: (1) a sample injection cup in fluid tight communication with a flow cell analyzer for measuring at least one electrolyte in a liquid sample and (2) an ion selective electrode analyzing station pump mechanism for pumping ion selective electrode analyzing station reagent from a source of ion selective electrode analyzing station reagent to the sample injection cup and for pumping the contents of the sample reaction cup through the flow cell analyzer and then to a suitable disposal site;

(g) a motorized sample probe arm assembly attached to the body, the sample probe arm assembly including (1) a sample probe arm and (2) a hollow sample probe having an internal chamber, an open lower end and an open upper end, the sample probe being disposed generally vertically, the sample probe being vertically movable between a lower sample probe position and an upper sample probe position, the sample probe arm being movable between a first

5 sample probe arm position wherein the sample probe is immediately above the sample extraction site and a second sample probe arm position wherein the sample probe is immediately above the cuvette sample deposit site;

(h) a sample probe pressure altering mechanism for alternatively applying a positive pressure and a negative pressure to the interior
10 chamber of the sample probe;

(i) a motorized reagent probe arm assembly attached to the body, the reagent probe arm assembly including (1) a reagent probe arm and (2) a hollow reagent probe having an internal chamber, an open lower end and an open
15 upper end, the reagent probe being disposed generally vertically, the reagent probe being vertically movable between a lower reagent probe position and an upper reagent probe position, the reagent probe arm being movable between a first reagent probe arm position wherein the reagent probe is immediately above the reagent extraction site and a second reagent probe arm position wherein the reagent probe is immediately above the cuvette reagent deposit site;

(j) a reagent probe pressure altering mechanism for alternatively applying a positive pressure and a negative pressure to the interior
20 chamber of the reagent probe;

(k) a motorized cuvette stirring rod arm assembly attached to the body, the cuvette stirring rod arm assembly including an elongate rotatable
25 cuvette stirring rod having a lower end and an upper end, the lower end of the cuvette stirring rod including a cuvette stirring rod paddle attached thereto, the cuvette stirring rod being disposed generally vertically, the cuvette stirring rod being movable between a lower cuvette stirring rod position and an upper cuvette stirring rod position, the cuvette stirring rod arm being positionable above the
30 cuvette mixing site;

(l) a cup analysis probe arm assembly attached to the body, the cup analysis probe arm assembly including (1) a motorized cup analysis probe arm and (2) a hollow, motorized cup analysis probe having an internal chamber,
35 an open lower end and an open upper end, the cup analysis probe being vertically movable between a lower cup analysis probe position and an upper cup analysis probe position, the cup analysis probe arm being movable between a first cup

5 analysis probe arm position wherein the cup analysis probe is immediately above a sample container, a second cup analysis probe arm position wherein the cup analysis probe is immediately above the reaction cup and a third cup analysis probe arm position wherein the cup analysis probe is immediately above the injection sample cup;

10 (m) a cup analysis probe pressure altering mechanism for alternatively applying a positive pressure and a negative pressure to the interior chamber of the cup analysis probe;

(n) a cuvette wash station attached to the body, the cuvette wash station including a hollow motorized cuvette wash station probe having an
15 internal chamber, an open lower end and an open upper end, the cuvette wash station being disposed such that the cuvette wash station probe is immediately above the cuvette washing site; and

(o) a sample container loading and preparation assembly comprising (1) a loading mechanism for moving one or more vertically disposed
20 capped sample containers from the loading area to the sample station along a loading mechanism path, wherein the elevation of the caps of the sample containers is E, and (2) a combination for piercing the cap of the sample containers disposed along the loading mechanism path, such combination comprising:

25 (i) a blade support arm slidably attached to a substantially vertical post such that the blade support arm is capable of travel along the vertical post between an upper blade support arm position, a middle blade support arm position and a lower blade support arm position, the blade support arm having an upper contact surface and a lower contact surface;

30 (ii) a blade attached to the blade support arm and disposed substantially vertically below the blade support arm, the blade being capable of piercing the container cap by downward movement of the blade;

(iii) a cap retainer arm having a cap contacting surface capable of contacting and retaining the container cap, the cap retainer arm being
35 slidably attached to the vertical post such that the cap retainer arm is capable of travel along the vertical post between the blade support arm upper contact

5 surface and the blade support arm lower contact surface;

(iv) a biasing member for biasing the cap retainer arm towards the blade support arm lower contact surface; and

(v) a motor for sliding the blade support arm up and down along the vertical post between the upper blade support arm position, the middle blade support arm position and the lower blade support arm position;

10 wherein, (i) at the upper blade support arm position, the blade support arm lower contact surface retains the cap retainer arm so that the cap contacting surface is higher than E, (ii) at the middle blade support arm position, the cap contacting surface is allowed to contact a container cap disposed at E but the blade is disposed higher than E and (iii) at the lower blade support arm position, the cap contacting surface is allowed to contact a container cap disposed at E and the blade is disposed below E; and

(p) a motor controller for controlling the operation of the sample station motor, a reagent station motor, a random access analyzing station motor, a reaction cup analyzing station pump, an ion selective electrode analyzing station pump mechanism, a sample probe arm motor, sample probe positioning mechanism, a sample stirring rod rotating motor, a sample probe pressurizing mechanism, a reagent station arm motor, a reagent probe positioning mechanism, a reagent stirring rod positioning motor, a reagent stirring rod rotating motor, a random access analyzing station motor, a cuvette wash station probe positioning motor cup analysis probe arm motor, a cup analysis probe positioning mechanism, a cup analysis stirring rod rotating motor and cup analysis probe pressurizing mechanism, the cap piercing motor and the loading mechanism.

30 14. The combination of claim 13 wherein the blade support arm and the cap retainer arm are slidably attached to a pair of substantially vertical posts disposed in parallel.

35 15. The combination of claim 13 wherein the blade comprises three or more piercing sections, each piercing section being disposed in a vertical plane and all of the vertical planes being disposed so that they intersect along a single

5 vertical axis with each plane being spaced apart from adjoining planes by equal angles.

16. The combination of claim 13 wherein each blade section comprises a point which has the shape of a right triangle and wherein the point of each
10 piercing section is disposed further from single vertical axis than any other portion of the piercing section.

17. A method for extracting a liquid sample from a sample container containing a quality of the sample, the sample within the sample container having
15 a meniscus and the sample container having a sealing cap, the method comprising the steps of:

- (a) mechanically transporting the sample container along a loading mechanism path to a location proximate to a cap piercing mechanism which comprises a moveable blade;
- 20 (b) piercing the sealing cap by mechanically thrusting the blade through the sealing cap and into the sample container;
- (c) mechanically removing the blade from the sample container and mechanically transporting the sample container further along the loading mechanism path to a sample station;
- 25 (d) extracting liquid sample from the sample container by mechanically thrusting a hollow probe through the pierced sealing cap to below the sample liquid meniscus and drawing a portion of the sample into the probe; and
- (e) mechanically removing the probe from the sample container.

177




Fig. 1




Fig. 2




Fig. 3

SUBSTITUTE SHEET (RULE 26)

37




Fig. 4A




Fig. 4C




Fig. 4B




Fig. 5E





Fig. 5D

4/7



110

Fig. 5A




Fig. 5B








Fig. 5C



SUBSTITUTE SHEET (RULE 26)



SUBSTITUTE SHEET (RULE 26)




Fig. 10A




Fig. 10B




Fig. 10C

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 G01N35/10

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 G01N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 90 11752 A (CLEANTECH S C I AB) 18 October 1990 see page 32, line 6 - line 20: figures 4-6	1-5, 9, 10, 13, 14, 17
A	EP 0 564 970 A (HOFFMANN LA ROCHE) 13 October 1993 see column 5, line 46 - column 7, line 24; figures 9-11	1-3, 6, 8, 9, 11, 13, 15, 17
A	US 4 721 137 A (MUELLER PAUL) 26 January 1988 see figures 1, 2	1-3, 6, 8, 9, 11, 13, 15, 17

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

10 March 1998

Date of mailing of the international search report

18/03/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Hodson, M